

Ergo Line Single

Compressor cooling



Product description

Ergo Line Single is made to hold and transport cold food safely and easily. The box is designed with ScanBox ExP construction that combines optimized insulation performance with high operational reliability and environmentally conscious choices.

The box is equipped with compressor cooling that provides effective temperature distribution down to 3°C in 30 minutes. Digitally adjustable temperatures

ensure excellent food quality control. ScanBox Ergo Line is available in several sizes with a capacity of up to 14 containers in the GN 1/1 standard.

Equipped with ScanBox Digital Control, excenter lock, solid door, 160 mm lockable wheels, removable U-guide rails with 80 mm spacing, black RAL 9005, 220-230V single phase as standard. The equipment can be easily adapted as required through available extra options.

Do you want to know more?

Contact us at info@scanbox.se
or +46 (0)454-30 83 00

ScanBox
Bringing your food with care

Technical specification

MODEL SERIE: Ergo Line Single - Compressor cooling



Product models	ELSCC06	ELSCC08	ELSCC10	ELSCC12	ELSCC14
Properties					
Regulator	Digital	Digital	Digital	Digital	Digital
Cooling system	Compressor back mounted (std)	Compressor back mounted (std)	Compressor back mounted (std)	Compressor back mounted (std)	Compressor back mounted (std)
Capacity					
Tray system	GN 1/1	GN 1/1	GN 1/1	GN 1/1	GN 1/1
Distance between racks (mm)	80	80	80	80	80
Number of 65mm trays	6	8	10	12	14
Maximum load weight per rack (kg)	9	9	9	9	9
Distance to the first rack (mm)	80	80	80	80	80
Physical Attributes					
Inside depth (mm)	600 mm	600 mm	600 mm	600 mm	600 mm
Inside width (mm)	352 mm	352 mm	352 mm	352 mm	352 mm
Inside height (mm)	567 mm	727 mm	887 mm	1047 mm	1207 mm
Outside depth (mm)	870 mm	870 mm	870 mm	870 mm	870 mm
Outside width (mm)	540 mm	540 mm	540 mm	540 mm	540 mm
Outside height (mm)	957 mm	1117 mm	1277 mm	1437 mm	1597 mm
Volume (l)	100 l	154 l	187 l	221 l	255 l
Net weight (kg)	57 kg	64 kg	68 kg	70 kg	77 kg
Spiral Cord	4.5 m	4.5 m	4.5 m	4.5 m	4.5 m
Electrical Attributes					
Rated voltage (V)	220-240 V	220-240 V	220-240 V	220-240 V	220-240 V
Rated frequency (Hz)	50-60 Hz	50-60 Hz	50-60 Hz	50-60 Hz	50-60 Hz
Power Rating (A)	0.88 A	0.95 A	0.95 A	0.95 A	0.95 A
Power (W)	135 W	135 W	135 W	135 W	135 W
IP code	22	22	22	22	22
Decibel	56	56	56	56	56

Equipment & Accessories

MODEL SERIE: Ergo Line Single - Compressor cooling



Castors & Brakes

Default	Castors 160 mm swiveling with brake
1000007	Castors 160 mm, stainless steel, swiveling with brake
1000009	Castors 160 mm, all swiveling w. brakes
1000010	Castors 160 mm, stainless steel, all swiveling w. brakes
1000016	Castors 200 mm w. central brake
1000008	Castors 160 mm, dish washable w. brake
1000004	Castors 200 mm swiveling with brake
1000005	Castors 160 mm reinforced, swiveling with brake
1000015	Castors 160 mm w. central brake
341006-1	Castors 400 mm Cross Country
1000006	Castors 200 mm reinforced, swiveling with brake
1000017	Castors 160 mm stainless steel w. central brake

Exterior

Default	Black (RAL 9005)
303010-2	Signature Logo
302030-1	Grey (RAL 7042)
950001	Signature Cover
302020-1	Red (RAL 3003)

Electric System

Default	220-240V - Type CEE 7/7
898294-1	220-240V - Type K
905390	220-240V - Type H
4000556	220-240V - Type L
898208-1	220-240V - Type J
90001	220-240V - Type C
898205-1	220-240V - Type G
905817	220-240V - Type I
898202-1	220-240V - Type G 1,5mm ²
90004	220-240V - Type O
898203-1	220-240V - Type I
90002	220-240V - Type D
4000241	220-240V - Type M

Door

Default	Solid
93002	Glass window
93003	Glass door
93004	Glass door with LED-Lights

Door Handle

Default	Excenter Lock
361004	TapSlam
351008-2	One Grip Handle with Lock
301054-1	One Grip Handle

Logistic System

302005	Ergonomic Base 320 mm
302006	Ergonomic Base 160 mm
361020	Central Brake
302002-2	Tow Bar Stainless Steel
302001-3	Tow Bar VE

Extras

301058-1	Vertical Push Handle
----------	----------------------

Accessories

400010-1	Card Holder
400003-1	Eutectic Plate GN 1/1
400001-1	Eutectic Plate Holder Ergo Line
301005-5	Aluminium Shelf GN 1/1
301014-7	Grid Stainless Steel GN 1/1

www.scanbox.se

Visiting adress ScanBox AB, Ekängsvägen 1. SE-293 40 Olofström, Sweden
Post adress ScanBox AB, P.O. Box 13. SE-293 21 Olofström, Sweden
Telephone +46 (0) 454 30 83 00 | Fax +46 (0) 454 30 83 30
Email info@scanbox.se | VAT SE556446828701

ScanBox
Bringing your food with care